



YDPU2.E48762 Tubing, Extruded Insulating - Component

Page Bottom

Tubing, Extruded Insulating - Component

See General Information for Tubing, Extruded Insulating - Component

SUMITOMO ELECTRIC FINE POLYMER INC

E48762

1-950 ASASHIRO NISHI

KUMATORI-CHO

SENNAN-GUN, OSAKA 590-0458 JAPAN

Cat. No.	Max V	Temp C	Shrinkdown Class@	Col Recognized	Max Temp Rated Oil Resistance C	VW-1 Rated #
Polyvinyl chloride (PVC).						
816	300	105	—	Clear	—	Yes
817	600	105	—	Clear	—	Yes
Irradiated polyvinyl chloride (PVC).						
806	300	105	—	+	—	Yes
807	600	105	—	+	—	Yes
Heat shrinkable polyvinyl chloride (PVC).						
818	300	105	1	Clear	—	Yes
819	600	105	1	Clear	—	Yes
823	300	105	1	Clear	—	Yes
Irradiated heat shrinkable polyvinyl chloride (PVC).						
808	300	105	I	+	—	Yes
809	600	105	I	+	—	Yes
822	300	105	I	+	—	Yes
Irradiated flexible heat shrinkable polyolefin.						
810 or Sumitube F	600	105	I	+	—	Yes
Sumitube F(T)	600	105	II	+	—	Yes
811 or Sumitube F2	600	125	I	+	—	Yes
820 or Sumitube F	600	105	I	+	—	Yes
821 or Sumitube F2	600	125	I	+	—	Yes
705 or Sumitube FPAC	600	125	I	+	—	Yes
826 or Sumitube B2*	600	125	I	+	—	Yes
B35*	600	125	I	+	—	Yes
Sumitube F5	600	125	I	+	—	Yes
939 or Sumitube F(Z)	600	105	I or II@	+	—	Yes
940 or Sumitube F2(Z) or Sumitube T82	600	125	I	+	—	Yes
958 or SM12	600	125	I	+	—	Yes
963 or SM23	600	125	I	+	—	Yes
SM3-12, SM3-23	600	125	I	+	—	Yes
938 or Sumitube F(TZ)	600	105	II	+	—	Yes
982 or B2(Z)	600	125	I	+	—	Yes
B2(3XZ) or B2(Z)4X	600	125	I	+	—	Yes

Sumitube F22(Z)	600	125	I	+	—	No
Sumitube F32	600	125	I	+	—	Yes
Sumitube F32(Z)	600	125	I	+	—	Yes
Sumitube F5(Z)	600	125	I	+	—	Yes
717 or Sumitube NHR2	600	125	I	\$	—	Yes
Irradiated semi-rigid heat shrinkable polyolefin.						
846 or Sumitube B8	600	125	I	+	—	Yes
967 or Sumitube FC3	600	125	I	+	—	Yes
Flexible heat shrinkable polyolefin tubing.						
Sumitube F32 a	600	125	—	+	—	Yes
Sumitube F34 a	150	125	—	+	—	Yes
Sumitube HF2	600	125	—	Black	—	Yes
Flexible not heat shrinkable polyolefin tubing.						
Irraxtube NHR4 or 719	300	125	—	\$	—	Yes

+ All colors except clear.

Tubing is considered to comply with the optional VW-1 flammability requirements only if it is so marked.

@ Shrink down class may appear on tag, label or smallest unit shipping container.

* May be followed by suffix 3X, Y/G, FLT or (3X)FLT.

\$ - Pink, yellow, blue, green, red, and black.

Marking: Company name, file number "E48762", or trade names "IRRAX", "SUMITUBE" or "SUMI-PAC", and catalog number, temperature rating in degrees C, voltage rating, date of manufacture and inside diameter (before and after recovery), shall be marked on tags attached to both ends of the tubing, on the shipping spool label or on the smallest unit container.

Last Updated on 2010-12-22

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

Copyright © 2011 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

